



ET200N

GPS Vehicle Tracker



Remote cut-off (petrol/power)

Compel the vehicle to stop by breaking off the fuel connection



IP65 water proof

Water-resistant case to ensure stable operation in tough environment



ACC detection for ignition status

Be aware of the ignition status whenever you need



9-90V voltage range

Wide operating voltage applicable to all types of vehicles



Configurable tracking modes

Location uploaded following fixed distance, time interval, preset cornering



Multiple alarms

Instant alert for vibration, overspeed, power off, geo-fence



Vehicle battery protection

Never drain out of the battery of motorcycle for optimal protection



Tracked by: SMS, APP, Web

Report location in real time through different interfaces

Application



Fleet management



Vehicle tracking



Motorcycle

GSM Specification

GSM frequency	850/900/1800/1900 MHz
GPRS	Class 12, TCP/IP
Memory	32+32Mb
Phase error	RMSPE<5,PPE<20
Max output	GSM850/GSM900:33±3dBm GSM1800/GSM1900:30±3dBm
Max frequency error	±0.1ppm

GPS Specification

GPS chipset	MTK high sensitivity chip
Frequency	L1, 1575.42MHz C/A code
GPS channel	66
Location accuracy	<10 meters
Tracking sensitivity	-162dBm
Acquisition sensitivity	-148dBm
TTF (open sky)	Avg. hot start ≤1sec Avg. cold start ≤35sec

Function & Package

Battery	270mAh/3.7V Li-Polymer battery
Working voltage/current	9-90VDC/7mA(60VDC)
Standby time	60 hours
Working time	3 hours
Operating temperature	-20℃~ 70℃
Device weight	41g
Device dimension	81.0(L)*43.0(W)*10.0(H)mm

Contact

Jimi Electronic Co., Ltd
Shenzhen Concox Information Technology Co., Ltd

Add: 4F, Building B, Gaoxinqi Industrial Park, Liuxian 1st Road, No.67 Bao'an District, Shenzhen

Tel: +86 755 6664 2520

Web: www.iconcox.com www.jimilab.com

Email: info@concox.cn info@jimilab.com