



Wetrack Lite

Vehicle GPS Tracker



GPS + LBS positioning

Allow the location to be pinpointed in real time or periodically



Hidden LED

Whoever uses your car will never know he or she's being tracked



IPX5 waterproof

Water-resistant to ensure stable operation in tough environment



Multiple alarms

Instant alerts for overspeed, low battery, vibration, etc



Compact size

Be able to place it in various locations throughout the vehicle



ACC detection

Be aware of the ignition status whenever you need

Application



Fleet Management



Vehicle rental



Logistics

GSM Specification

Communication system	GSM
GSM frequency	850/900/1800/1900MHz
GPRS	Class 12, TCP/IP
Memory	32 + 32 Mb
Phase error	RMSPE<5, PPE<20
Max output	GSM850/GSM900:33±2dBm GSM1800/GSM1900:30±2dBm
Max frequency error	±0.1ppm
Receive sensitivity	Class II RBER2%(-102dBm)

GPS Specification

Chipset	High sensitivity GPS chips
Frequency	GPS L1, 1575.42MHz
Channel	66
Location accuracy	<10 meters
Tracking sensitivity	-165dBm
Acquisition sensitivity	-148dBm
TTF (open sky)	Avg. hot start ≤1sec Avg. cold start ≤32sec

Function & Package

GSM/GPS antenna	Built-in quad band GSM antenna, GPS ceramic antenna
LED indicator	GPS(blue), GSM(green)
Working voltage/current	9-36VDC/32mA(12VDC)18mA(24VDC)
Standby current	≤5mA
Operating temperature	-20℃ ~+70℃
Waterproof rate	IPX5
Battery	100mAh / 3.7V industrial grade lithium battery
Device weight	26.6g
Device dimension	73.8(L)× 25.9(W)× 12.2(H)mm

Contact

Shenzhen Concox Information Technology Co., Ltd

Add: 4/F, Building B, Gaoxinqi Industrial Park, Liuxian 1st Road, No.67 Bao'an District, Shenzhen

Tel: +86 755 6664 2520

Web: www.iconcox.com www.jimilab.com

Email: info@concox.cn info@jimilab.com